



COMMERCIAL STEEL FRAMES & DOORS



- ✓ FREE order coordination from approved submittals
- ✓ Will work from other manufacturer's nomenclature
- ✓ Just in Time: Expediting, Standard, and Project Lead Time

DOORS

- Gauges: 18, 16, and 14
- Material: Galvanneal Steel (A40 and A60), and Stainless steel (316 and 304 #4 finish)
- Construction: butte edge (BE) and mechanical interlock (MI)
- Edges: seamed (MI only), seamless filled (MI only), and continuously welded (BE only)
- Cores: Honeycomb (standard), polystyrene, steel ribbed insulated, polyurethane (polyisocyanurate), mineral board (temprise).
- Hardware preps: per manufacturer's template, ANSI A156, and SDI 250.6.
- Lites: Integral (standard) or cutout only.
- Louvers: National Guard (ship loose) or cutout only.
- Fire Rating: UL, up to 3HR, Temp Rise 450, max door size is 5'0" x 12'0" single or 10'0" x 12'0" pair.

FRAMES

- Gauges: 18, 16, and 14
- Material: Galvanneal Steel (A40 and A60), and Stainless steel (316 and 304 #4 finish)
- Welds: Face, CDM Continuous (face + soffit), Full Profile, and KD.
- Profiles: Double equal rabbit (standard), single rabbit, cased open, center glazed, custom.
- Anchors: welded (standard), wire anchor, T anchor, punch and dimple, or compression anchor.
- Hardware preps: per manufacturer's template, ANSI A156, and SDI 250.6.
- Shop Splices: will exceed 10ft limits in certain cases.
- Fire Rating: UL; max door size is 5'0" x 12'0" single or 10'0" x 12'0" pair.
- Lead Lined: 1/32, 1/16, or 1/8.
- Thermal Break frames



Crating

LTL - Less Than Load

Box Truck

Pool Truck (bestway)

Dedicated Dry Van

CONTACT US

Phone: (505) 881-1034 | Toll Free: (866) 494-7687
 For Sales: Option 2 or quotes@commercialdoormfg.com
 For Ordering or Service: Option 1 or orders@commercialdoormfg.com

Factory Location: Albuquerque, New Mexico

Mailing Address: 8201 Golf Course Rd. NW
 Suite D3-296
 Albuquerque, NM 87120

