

# Commercial Door Manufacturing, Inc.

2914 Girard NE, Albuquerque, NM 87107

CommercialDoorMfg.com

505-881-1034

(fax) 505-884-1484

## Door Elevations

**F**

**V1**

**G1**

**S1**

**G21**

**L1**

**CYLINDRICAL LOCKS TO BE 40-5/16" TO CL OF STRIKE ABOVE FINISHED FLOOR.**

**MORTISE LOCKS TO BE 40-5/16" TO CL OF STRIKE ABOVE FINISHED FLOOR.**

**DEAD LOCKS TO BE 48" TO CL OF STRIKE ABOVE FINISHED FLOOR.**

**PANICS PER MANUFACTURERS TEMPLATE.**

	ELEV	W	H	FH	ELEV	LS	TS	H	ELEV	LS	TS	W	H	ELEV	LS	TS	H	ELEV	W	H	BD	TYPE	
	V1				G1				S1					G21				L1					
	V2				G2				S2									L2					
	V3				G3				S3					G22				L3					
	V4				G4				S4									L4					
	V5				G5				S5					G23				L5					
	V6				G6				S6									L6					
	V7				G7				S7					G24				L7					
	V8				G8				S8									L8					
	V9				G9				S9									L9					

**DD**

SILL 1    SILL 2    SILL 3

1/4" GLASS THICKNESS OR AS SPECIFIED

1" GLASS THICKNESS OR AS SPECIFIED

LOUVERS Y TYPE

ASTRAGAL

12 GA. X 1 1/2" LOOSE

DOOR EDGE CONSTRUCTION

MECHANICAL INTERLOCK-SEAMED OR SEAMLESS SEE COVER SHEET

CONTINUOUSLY WELDED, GROUND SMOOTH - BUTT EDGE - SEAMLESS

**NOTE: DOOR GLASS SIZES ARE NET VISUAL AREA, TYPICAL. FIELD MEASURE FOR GLAZING**

**HOLLOW METAL DOOR ELEVATIONS**

GA	DOOR REINFORCEMENT	DOOR REINFORCEMENT	MISCELLANEOUS
3/16"	HINGE	HONEYCOMB	* ALL GLASS DIMENSIONS ARE NET VISUAL AREAS, TYPICAL
12	LOCK	POLYSTYRENE	* CLEARANCES = 1/8" BETWEEN PAIRS. 1/8" AT JAMBS AND HEADS
12	CLOSER	STEEL RIB / GA. (INSULATED)	* FOR PAIR OF DOORS USE PREFIX '2' (I.E. 2F, 2V1, 2L1, ETC.)
GA	DOOR FACE SHEETS	DOOR EDGE	DOOR SERIES
16	EXTERIOR	SEAMED	BUTT EDGE
16	INTERIOR	SEAMLESS	MECH INTERLOCK
GRAY	PRIME COAT		

**NOTE:**

ALL DIMENSIONS ON THIS SHEET ARE IN INCHES.

DOOR - FLUSH TOP CAP EXTERIOR DOORS TYPICAL

PROJECT:
ARCHITECT:
CONTRACTOR:
PROJECT NO:
DATE:
SHEET:
DOOR ELEVATIONS / SPECIFICATIONS